

# PHS Primer

Adhesive PHS Primer Paint is a dispersion-based polyacrylate.

It is a low to medium viscosity prime coat.

Designed to prepare rough and sandy application surfaces for airtightness tape adhesion.

## Application

- Apply PHS Primer on the surface to be bonded.
- Let the primer dry well before further processing of the surface.
- The applied primer should feel mostly dry.
- Apply several times on difficult substrates, if necessary, and allow to dry well each time.
- Apply the adhesive tape on the treated surface and press firmly at once. Observe the instructions for use of the respective adhesive tape.

## Advantages

- Ideal for: wooden construction materials, masonry and concrete.
- Easy and even to apply.
- Quick-drying.

## Processing

- Apply PHS Primer on the surface to be bonded.
- Let the primer dry well for further processing – the surface of the applied primer should feel mostly dry.
- Apply several times on difficult substrates, if necessary, and allow to dry well each time.
- Apply the adhesive tape on the treated surface and press firmly at once. Finally – please observe the instructions for use of the respective adhesive tape.

## Consumption Value (per 1 kg)

- Stone/concrete approx 12m<sup>2</sup>.
- Fire boards approx 6m<sup>2</sup>.



## Technical Data

Basis	polyacrylate dispersion
Temperature range after application	-20 °C to + 0 °C
Shelf life	in unopened can, 12 months
Typical Consumption Rate (per 1 kg)	
Stone/concrete	approx. 12 m <sup>2</sup>
Fireboards	approx. 6 m <sup>2</sup>